



Woods

Operator's & Parts Manual

L59KL-3 and LU306KL-1

Rotary Mower for

Kubota L200, L200A,

L210 and L260 Tractors

or Call 800-443-0622

JENSALES

THIS IS A MANUAL PRODUCED BY JENSALES INC. WITHOUT THE AUTHORIZATION OF
WOODS OR IT'S SUCCESSORS. WOODS AND IT'S SUCCESSORS
ARE NOT RESPONSIBLE FOR THE QUALITY OR ACCURACY OF THIS MANUAL.

TRADE MARKS AND TRADE NAMES CONTAINED AND USED HEREIN ARE THOSE OF OTHERS,
AND ARE USED HERE IN A DESCRIPTIVE SENSE TO REFER TO THE PRODUCTS OF OTHERS.

WD-OP-L59KL3

Operator's & Parts Manual

CLICK ANYWHERE FOR MORE DETAILS

Ed

WOOD BROTHERS Inc.

SUBSIDIARY OF **HESSTON** CORPORATION

SALES AND SERVICE THROUGHOUT
THE UNITED STATES AND CANADA

OREGON, ILLINOIS 61061 • VICKSBURG, MISSISSIPPI 39181

OWNER'S MANUAL AND PARTS LIST (WITH ASSEMBLY INSTRUCTIONS)



For Use On
Kubota
L200, L200A, L210
& L260 Tractors

(Includes Repair Information
for Older Models)

MODEL NO.
L59KL-3
LU306KL-1

WOOD'S Rotary Mower

F-5598 (Rev. 4-73)

CLICK ANYWHERE FOR MORE DETAILS

File# L59KL-3

BELT ASSEMBLY & ADJUSTMENT INSTRUCTIONS

Models Used On: 59C, L59 & LU306, Models BMC, D, D10-D12
F, JM, K22, KD, KL, H3, H4, H5, MF, M25, S, VC, U, Etc.

L59,
LU306

1. First put belt on the bottom groove, right hand side of the center sheave. Then thread it to the left, around the left hand sheave.

2. Bring the belt back across the center sheave in the center groove over to the right outside sheave.

3. Then thread it back across the front of the center sheave in the top groove.



4. Proper Twist: The belt then follows with a $3/4$ twist back under the left V-idler, up over the drive sheave and back down under the right idler pulley. This will leave a $1/4$ twist in the section of belt extending from the right V-idler to lower groove of the center mower sheave.

5. Adjust the mower to proper cutting height. The front of the mower should be slightly lower than the rear for the best cutting and least power requirement.

6. Idler Adjustment: Make minor belt adjustments with idlers but keep left idler about 1" above being in line with the groove in which the belt runs on the center sheave of the mower and right idler about 1" below. Move mower fore and aft for major adjustments. On LU306KL use belt takeup idlers on mower deck for major adjustment.

or Call 800-223-0625

L59,
LU306

ALWAYS USE 1000 RPM PTO SPEED

Remove tractor pin. Install $3/4 \times 1 \times 3/16$ sleeve on nut side of pin. Install bracket (14) over sleeve and reinstall pin. The casting, which attaches lift arm adjusting screw to upper rock shaft arm, should be turned around for better fit.

FOR L200 &
L210 TRACTORS

Bolt brackets (6), (8), & (9) together here

Bolt bar (7) to push arm (6). Attach sway chain to bar (7). Adjust this hole in bar so it is in line with 3 pt lift arm pivot.

Belt makes $3/4$ twist here

Belt makes $1/4$ twist here and ahead of right V-idler

Shaft protrudes through bushing about $1/4$ "

L59KL & LU306KL MOUNTING FRAME ASSEMBLY PHOTO

Used on Kubota L260

Page 9

